

OTR10XHSL200



Camera	
Image Sensor	1/2.9" Low Illumination 2.1MP CMOS Sensor
Resolution	2MP
Compression	H.264
S/N Ratio	>50db

PTZ	
Horizontal Rotation Speed	30 ° / S
Horizontal Rotation Range	0 ° ~ 180 °
Tilt Rotation Speed	25 ° / S
Tilt Rotation Range	-45 ° ~ 40 °
Preset Points	220
Guard Tours	3 groups
Guard Points	Max. 16 points

Lens	
Focus Length	5.1mm – 51mm
Focus Control	10X Optical Zoom

Night Vision	
Infrared LED	4PCS Array IR LEDES + 2 PCS Laser Lamp
IR Range	100m
Day-night mode	AUTO

Interface	
Audio	Optional
Alarm	/
SD Card Slot	/
POE	Optional

Network	
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA
Main Stream 1	2304*1296@20fps
Main Stream 2	1920*1080@30fps
Sub Stream 1	800*448@30fps
Sub Stream 2	704*576@30fps
Sub Stream 3	640*360@30fps
Sub Stream 4	352*288@30fps

General	
Weatherproof	IP66
Operating Temperature	Indoor: 0° ~ +40° Outdoor: -40° ~ +60°
Operation Humidity	≤90% Non Condensing
Power	DC12V / 3A
Lightning Protection	Transient voltage 6000V
Dimension	39.6 X 19.6 X 16 (cm)
Weight	3 kg