

4CH Network Video Recorder



- Support Ultra 265/H.265/H.264 video formats
- 4-channel input
- Third-party IP cameras supported with ONVIF conformance
- 1 SATA HDD up to 6TB

Specifications

Model	OTR3104
Video/Audio Input	
IP Video Input	4-ch
Network	
Incoming Bandwidth	64Mbps
Outgoing Bandwidth	48Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
HDMI/VGA Output	HDMI: 3840x2160/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Audio Output	1-ch, RCA
Synchronous Playback	4-ch
Corridor Mode Screen	3/4/5/7/9
Decoding	
Decoding format	Ultra265/H.265/H.264
Live view/Playback	4-ch
Capability	4-ch@1080p
Hard Disk	
SATA	1 SATA interfaces
Capacity	Up to 6TB for each disk
Smart	
VCA Detection	Face detection, Intrusion detection, Cross line detection, Audio detection
VCA Search	Face search, Behavior search
External Interface	

Network Interface	1 RJ-45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel: 2 x USB2.0
General	
Power Supply	12V DC Power Consumption: ≤ 5 W (without HDD)
Working Environment	-10°C~+ 55°C (+14°F~+131°F), Humidity $\leq 90\%$ RH (non-condensing)
Dimensions (W×D×H)	260mm × 240mm × 46 mm (10.2" × 9.4" × 1.8")
Weight (without HDD)	≤ 0.98 kg (2.16lb)

Dimensions

