


32CH Network Video Recorder



- Support Ultra 265/H.265/H.264 video formats
- 32-channel input
- Third-party IP cameras supported with ONVIF conformance
- 4 SATA HDDs, up to 12TB for each HDD

Specifications

Model	OTR9832
Video/Audio Input	
IP Video Input	32-ch
Two-way Audio Input	1-ch, RCA
Network	
Incoming Bandwidth	320Mbps
Outgoing Bandwidth	320Mbps
Remote Connection	Up to 32 Users
Protocols	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, UPnP, HTTP
API	API/Onvif (profile S/G/T)
WEB	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
Performance	
Recording Compression	Audio: G.711a,G.711u Video : H.264/H.265、H.264+/H.265+
Speed	4K:120fps 4MP:240fps 2MP:480fps
Playback	1080P:480fps Max 16CH
Interface	
HDMI	1 (1024*768,1280*720,1280*1024,1440*900,1920*1080,2560*1440(2K),3840*2160(4K))
	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 /EDID) Async out
USB	USB2.0*1(front) USB3.0*1+USB2.0*1(rear)
Audio	1 in / 1 out

E-sata	1
HDD	4 ,each up to 12TB
RS485	1
Alarm Input/out	16 in /4 out
Disk Array	
Array Type	RAID 1, 5
General	
OSD Language	English/French/Spanish/Portuguese/German/Italian/Greek/Danish/Finnish/Russia/Hebrew/ Turkish/Bulgarian/Arabic/Korean/Japanese/Thai/Hindi/Romanian/Dutch/Polish
Dimension (WxDxH)	378*326*66mm
Weight	6645g
Input Voltage/Current	12V/5A
Power consumption (excluding hard disk)	8W
Operating Temperature	0°C~+50°C (32°F ~ 122°F)
Operating Humidity	Less than 90%RH