

4MP(2K) IR POE 360PTZ Network Camera



- IR POE PTZ Camera
- H.264/H.264+/H.265/MJPEG
- 25x Optical Zoom
- IR distance up to 120m
- IP65 Waterproof

Specifications

Model	OTRAPTZ408
Camera	
Image Sensor	1/2.8" SONY Low Illumination CMOS Sensor
Resolution	4MP
Effective Pixels	2688(H)*1522(V)
Compression	H.264/H.264+/H.265/MJPEG
S/N Ratio	>50db
PTZ	
Horizontal Rotation Speed	80° /S
Horizontal Rotation Range	0° -360°
Tilt Rotation Speed	60° /S
Tilt Rotation Range	0° -93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	5.35mm - 96.3mm
Focus Control	25x Optical Zoom
Night Vision	
Infrared LED	Φ 42x6PCS IR LEDS + 2PCS Laser LED
IR Range	120m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, PPPoE, P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface, support 10M/100M IP DATA

Main Stream 1	1920*1080@30fps
Main Stream 2	1280*720@30fps
Sub Stream 1	800*448@30fps
Sub Stream 2	704*576@30fps
Sub Stream 3	640*360@30fps
Sub Stream 4	352*288@30fps
AI Function	
Smart Analytic	3D Human Tracking、Intrusion Detection、Alarm Detection
Tracking effective range	5 - 80M Speed: 3-12KM/h
Interface	
Audio	2-Way Audio
Alarm	/
SD Card Slot	/
POE	YES
General	
Weatherproof	IP65
Operating Temperature	-40°C - +70°C
Operating Humidity	≤90% Non-Condensing
Power	DC12V/4A
Lightning Protection	Transient voltage 6000V
Dimension	25.5 x 21.5 x 41.0 (cm)
Weight	3.1 kgs